



Safe-Set 2 (trowelable) and Safe-Set 602 (spray)
Premium Pressure Sensitive Adhesive

A premium pressure sensitive releasable adhesive designed for a variety of vinyl backed carpets, especially modular carpet tiles. This enhanced formula ensures adhesion for the most demanding recycled backings.

- High Moisture Technology - **MVER up to 10 lbs. / 90% RH**
- Persistent tack to grip carpet tile during installation, yet releasable to allow for ease of replacement
- Acrylic copolymer latex-based for exceptional plasticizer migration resistance
- LEED Compliant (VOC 0 g/L) and CRI Green Label Plus Certified



Safe-Set 7 (trowelable) and Safe-Set 607 (spray)
Premium Clear Thin Spread Adhesive

A premium-grade adhesive for the installation of Vinyl Composition Tile (VCT) and asphalt tile. This high solids formula provides excellent water resistance and offers an even faster tack, resulting in less downtime.

- High Moisture Technology - **MVER up to 10 lbs. / 90% RH**
- Formulated to provide immediate grab and quick-drying to expedite installations
- Provides the ability to bond new tile to old (tile-over-tile installation)
- Dries clear – allows chalk lines to remain visible during installation
- LEED Compliant (VOC 0 g/L) and CRI Green Label Plus Certified



Safe-Set 3
Premium Carpet Adhesive

A premium carpet adhesive specifically designed with extremely fast grab to hold down the most rigid backings. The ultimate choice for quick turnaround solutions throughout all commercial installations.

- High Moisture Technology - **MVER up to 8 lbs. / 86% RH**
- High solid formulation providing a tenacious bond
- Ideal for Double-Bond method of installation (carpet to pad)
- LEED Compliant (VOC 0 g/L) and CRI Green Label Plus Certified



CHAPCO 975
Premium Wet-Set Carpet Adhesive

A premium, high solids carpet adhesive for all closed cell carpet backings. The Wet-Set method provides a quick installation with excellent wet suction and no downtime.

- High Moisture Technology - **MVER up to 8 lbs. / 86% RH**
- Rapid-setting and drying times for accelerated installations
- Extremely high-strength adhesive to be used for the most demanding jobs
- LEED Compliant (VOC 0 g/L) and CRI Green Label Plus Certified



Safe-Set DB900
Double-Bond Carpet Adhesive

A premium, double stick carpet adhesive formulated with an extended open time for the installation of pattern match goods.

- High Moisture Technology - **MVER up to 8 lbs. / 86% RH**
- LEED Compliant (VOC 0 g/L) and CRI Green Label Plus Certified
- Extended open time (30-40 min) for the installation of pattern match goods such as Axminsters
- Extremely water resistant when cured



ASTM F 1869	ASTM F 2170
HMT at 8 lbs.	86% RH
HMT at 10 lbs.	90% RH