

## MATERIAL SAFETY DATA SHEET

---

REVISION DATE: 09-22-2010

SUPERSEDES: None

### SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

#### COMPANY INFORMATION

H.B. Fuller Construction Products Inc.  
1105 S. Frontenac Street  
Aurora, IL 60504  
Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758  
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

#### PRODUCT INFORMATION

PRODUCT NUMBER: CHAPCO PREMIUM SLU  
PRODUCT DESCRIPTION: Cement  
PRODUCT IDENTIFIER: 828724PM

### SECTION 2: HAZARDS IDENTIFICATION

---

#### EMERGENCY OVERVIEW

PHYSICAL STATE: Solid  
COLOR: Gray  
ODOR: Odorless

Moderate eye irritant.  
Causes skin irritation.  
Moderate respiratory tract irritant.  
Harmful if swallowed.  
Cancer hazard.

#### POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

EYE: Can cause moderate irritation, tearing and reddening.

SKIN: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

INHALATION: Can cause moderate respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Other possible symptoms include coughing or wheezing.

Nasal perforation is possible from a single large or repeated smaller inhalation overexposures.

Overexposure to crystalline silica may cause silicosis. Overexposure to iron oxide dust/fume may cause siderosis.

INGESTION: Ingestion is not an anticipated route of exposure. Harmful if swallowed. Severely irritating to mouth, throat, and stomach.

#### LONG-TERM (CHRONIC) HEALTH EFFECTS

TARGET ORGAN(S): Lungs

#### REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

Crystalline silica

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Lung disease

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

---

Chemical Name	CAS #	PERCENT
Crystalline silica	14808-60-7	30 - 50

**MATERIAL SAFETY DATA SHEET**

Alumina cement	65997-16-2	10 - 30
Calcium carbonate	471-34-1	10 - 30
Calcium sulfate	7778-18-9	5 - 10
Portland cement	65997-15-1	5 - 10
Aluminum oxide	1344-28-1	1 - 5
Calcium oxide, CaO	1305-78-8	1 - 5
Iron oxide	1309-37-1	1 - 5
Calcium sulfate, hemihydrate	26499-65-0	1 - 5
Sulfur trioxide	7446-11-9	1 - 5
Magnesium Oxide	1309-48-4	1 - 5

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

**SECTION 4: FIRST AID MEASURES**

**IF IN EYES:** Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

**IF ON SKIN:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

**IF VAPORS INHALED:** Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

**IF SWALLOWED:** Severely irritating. Do not induce vomiting. Seek medical attention immediately. Drink 2 glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person.

**SECTION 5: FIRE FIGHTING MEASURES**

<b>FLASH POINT:</b>	Non flammable
<b>AUTOIGNITION TEMPERATURE:</b>	Not established
<b>LOWER EXPLOSIVE LIMIT (% in air):</b>	Not established
<b>UPPER EXPLOSIVE LIMIT (% in air):</b>	Not established
<b>EXTINGUISHING MEDIA:</b>	Use water spray, foam, dry chemical or carbon dioxide.
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS:</b>	Material will not burn.
<b>SPECIAL FIRE FIGHTING INSTRUCTIONS:</b>	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
<b>HAZARDOUS COMBUSTION PRODUCTS:</b>	Carbon dioxide, Carbon monoxide Sulfur containing gases Aluminum oxide

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**SPECIAL PROTECTION:** Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred.

**CLEAN-UP:** Avoid creating dusts. Cover material with absorbent and moisten and collect for disposal.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

## MATERIAL SAFETY DATA SHEET

### SECTION 7: HANDLING AND STORAGE

**Handling:** Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Avoid breathing material.

**Storage:** Store in a cool, dry place.

Consult the Technical Data Sheet for specific storage instructions.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**EYE PROTECTION:** Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.

**SKIN PROTECTION:** Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur.

**GLOVES:** Nitrile

**RESPIRATORY PROTECTION:** Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with dust/mist filter. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

**VENTILATION:** Use local exhaust ventilation or other engineering controls to minimize exposures.

#### EXPOSURE LIMITS:

Chemical Name	ACGIH EXPOSURE LIMITS	OSHA PEL
Crystalline silica	0.025 mg/m <sup>3</sup> TWA respirable fraction	((250)/(%SiO <sub>2</sub> + 5) mppcf TWA (respirable)); ((10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA (respirable)); ((30)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA (total dust))
Alumina cement	Not established	Not established
Calcium carbonate	Not established	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)
Calcium sulfate	10 mg/m <sup>3</sup> TWA inhalable fraction	15 mg/m <sup>3</sup> TWA total dust; 5 mg/m <sup>3</sup> TWA respirable fraction
Portland cement	10 mg/m <sup>3</sup> TWA particulate matter containing no asbestos and <1% crystalline silica	15 mg/m <sup>3</sup> TWA total dust; 5 mg/m <sup>3</sup> TWA respirable fraction
Aluminum oxide	Not established	15 mg/m <sup>3</sup> TWA total dust; 5 mg/m <sup>3</sup> TWA respirable fraction

**MATERIAL SAFETY DATA SHEET**

Calcium oxide, CaO	2 mg/m3 TWA	5 mg/m3 TWA
Iron oxide	5 mg/m3 TWA respirable fraction	10 mg/m3 TWA (as fume)
Calcium sulfate, hemihydrate	Not established	15 mg/m3 TWA total dust; 5 mg/m3 TWA respirable fraction
Sulfur trioxide	Not established	Not established
Magnesium Oxide	10 mg/m3 TWA inhalable fraction	15 mg/m3 TWA (total particulate) (as fume)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE:	Solid
COLOR:	Gray
ODOR:	Odorless
ODOR THRESHOLD:	Not established
WEIGHT PER GALLON (lbs.):	11.2
SPECIFIC GRAVITY:	1.34
SOLIDS (% by weight):	100.0
pH:	Not applicable
FLASH POINT:	Not established
BOILING POINT (deg. C):	Non flammable
FREEZING/MELTING POINT (deg. C):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established
EVAPORATION RATE:	Not established
OCTANOL/WATER COEFFICIENT:	Not established
VOC, weight percent	Not determined

**SECTION 10: STABILITY AND REACTIVITY**

STABILITY:	Stable under normal conditions.
CHEMICAL INCOMPATIBILITY:	Not established
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide Sulfur containing gases Aluminum oxide

**SECTION 11: TOXICOLOGICAL INFORMATION**

COMPONENT	LD50/LC50
Crystalline silica	Not established

## MATERIAL SAFETY DATA SHEET

---

Alumina cement	Not established
Calcium carbonate	Oral LD50 Rat = 6450 mg/kg
Calcium sulfate	Not established
Portland cement	Not established
Aluminum oxide	Not established
Calcium oxide, CaO	Not established
Iron oxide	Not established
Calcium sulfate, hemihydrate	Not established
Sulfur trioxide	Not established
Magnesium Oxide	Not established

TOXICOLOGY SUMMARY: No additional health information available.

---

### SECTION 12: ECOLOGICAL INFORMATION

---

OVERVIEW: No ecological information available

---

### SECTION 13: DISPOSAL CONSIDERATIONS

---

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Dispose of in an approved landfill. Consult your state, local or provincial authorities and your local waste vendor for more restrictive requirements.

---

### SECTION 14: TRANSPORTATION INFORMATION

---

Consult Bill of Lading for transportation information.

DOT: NOT REGULATED

IATA: NOT REGULATED

---

### SECTION 15: REGULATORY INFORMATION

---

#### INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt from DSL requirements.

EUROPEAN EINECS: As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.

If you need more information about the inventory status of this product call 651-236-5858.

**MATERIAL SAFETY DATA SHEET**

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at 651-236-5858 (USA) or 450-655-1306 x227 (Canada) to request an export review.

**FEDERAL REPORTING****EPA SARA Title III Section 313**

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
---------------	------	---

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2A D2B

**STATE REPORTING**

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List	CAS	Percent
Quartz (Carcinogen)	14808-60-7	30 - 50
Acetaldehyde (Carcinogen)	75-07-0	0.001 - 0.01
Chromium VI (Carcinogen)		< 10 ppm
Nickel (Carcinogen)		< 10 ppm
Lead compounds (Carcinogen)		< 10 ppm
Cadmium compounds (Carcinogen)		< 10 ppm
Arsenic compounds (inorganic) (Carcinogen)		< 10 ppm
Lithium carbonate (Developmental toxin)	554-13-2	0.01 - 0.1

**SECTION 16: ADDITIONAL INFORMATION**

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 0 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.